


DO-35(GLASS)



Dimensions in inches and (millimeters)

FEATURE

- Low zener impedance
- Low regulation factor
- Glass passivated junction
- High temperature soldering guaranteed:
260°C/10S/9.5mm lead length at 5 lbs tension

MECHANICAL DATA

Case: JEDEC DO-35(GLASS) molded glass body

Terminals: Plated axial leads, solderable per MIL-STD 750, method 2026

Polarity: Color band denotes cathode end

Mounting Position: Any

Weight: 0.005 ounce,0.14 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

	SYMBOLS	VALUE	UNITS
Zener Current see Table Characteristics			
Power Dissipation at Tamb=25°C(Note 1)	P _{tot}	500	mW
Junction Temperature	T _j	200	°C
Storage Temperature Range	T _{STG}	-65 to + 200	°C
Thermal resistance junction ambient(Note 1)	R _{θJA}	0.3	K/mW
Forward voltage at I _F =100mA	V _F	1.0	V


Note 1: Valid provided that leads at a distance of 10mm from case are kept at ambient temperature

ELECTRICAL CHARACTERISTICS (at TA=25°C unless otherwise noted)

Device Type	Nominal Zener Voltage Vz@Izr		Test Current Izr	Maximum Zener Impedance			Maximum Reverse Leakage Current		Typical Temperature Coefficient	Maximum Regulator Current Izm
	Min	Max		Zzt@Izr	Zzk@Izk	Izk	IR	@VR		
BZX55C2V4	2.28	2.56	5.0	85	600	1.0	50	1.0	-0.085	155
BZX55C2V7	2.5	2.9	5.0	85	600	1.0	10	1.0	-0.080	135
BZX55C3V0	2.8	3.2	5.0	85	600	1.0	4.0	1.0	-0.075	125
BZX55C3V3	3.1	3.5	5.0	85	600	1.0	2.0	1.0	-0.070	115
BZX55C3V6	3.4	3.8	5.0	85	600	1.0	2.0	1.0	-0.065	105
BZX55C3V9	3.7	4.1	5.0	85	600	1.0	2.0	1.0	-0.060	95
BZX55C4V3	4.0	4.6	5.0	75	600	1.0	1.0	1.0	±0.055	90
BZX55C4V7	4.4	5.0	5.0	60	600	1.0	0.5	1.0	±0.030	85
BZX55C5V1	4.8	5.4	5.0	35	550	1.0	0.1	1.0	±0.030	80
BZX55C5V6	5.2	6.0	5.0	25	450	1.0	0.1	1.0	+0.038	70
BZX55C6V2	5.8	6.6	5.0	10	200	1.0	0.1	2.0	+0.045	64
BZX55C6V8	6.4	7.2	5.0	8.0	150	1.0	0.1	3.0	+0.050	58
BZX55C7V5	7.0	7.9	5.0	7.0	50	1.0	0.1	5.0	+0.058	53
BZX55C8V2	7.7	8.7	5.0	7.0	50	1.0	0.1	6.2	+0.062	74
BZX55C9V1	8.5	9.6	5.0	10	50	1.0	0.1	6.8	+0.068	43
BZX55C10	9.4	10.6	5.0	15	70	1.0	0.1	7.5	+0.075	40
BZX55C11	10.4	11.6	5.0	20	70	1.0	0.1	8.2	+0.076	36
BZX55C12	11.4	12.7	5.0	20	90	1.0	0.1	9.1	+0.077	32
BZX55C13	12.4	14.1	5.0	26	110	1.0	0.1	10	+0.079	29
BZX55C15	13.8	15.6	5.0	30	110	1.0	0.1	11	+0.082	27
BZX55C16	15.3	17.1	5.0	40	170	1.0	0.1	12	+0.083	24
BZX55C18	16.8	19.1	5.0	50	170	1.0	0.1	13	+0.085	21
BZX55C20	18.8	21.2	5.0	55	220	1.0	0.1	15	+0.086	20
BZX55C22	20.8	23.3	5.0	55	220	1.0	0.1	16	+0.087	18
BZX55C24	22.8	25.6	5.0	80	220	1.0	0.1	18	+0.088	16
BZX55C27	25.1	28.9	5.0	80	220	1.0	0.1	20	+0.090	14
BZX55C30	28	32	5.0	80	220	1.0	0.1	22	+0.091	13
BZX55C33	31	35	5.0	80	220	1.0	0.1	24	+0.092	12
BZX55C36	34	38	5.0	80	220	1.0	0.1	27	+0.093	11
BZX55C39	37	41	2.5	90	500	0.5	0.1	30	+0.094	10
BZX55C43	40	46	2.5	90	600	0.5	0.1	33	+0.095	9.2
BZX55C47	44	50	2.5	110	700	0.5	0.1	36	+0.095	8.5
BZX55C51	48	54	2.5	125	700	0.5	0.1	39	+0.096	7.8
BZX55C56	52	60	2.5	135	1000	0.5	0.1	43	+0.096	7.0
BZX55C62	58	66	2.5	150	1000	0.5	0.1	47	+0.096	6.4
BZX55C68	64	72	2.5	200	1000	0.5	0.1	51	+0.096	5.9
BZX55C75	70	80	2.5	250	1500	0.5	0.1	56	+0.096	5.3
BZX55C82	77	87	2.5	300	2000	0.5	0.1	62	+0.096	4.8
BZX55C91	85	96	1.0	450	5000	0.1	0.1	68	+0.096	4.4
BZX55C100	94	106	1.0	450	5000	0.1	0.1	75	+0.096	4.0
BZX55C110	104	116	1.0	600	5000	0.1	0.1	82	+0.096	3.6
BZX55C120	114	127	1.0	800	5000	0.1	0.1	91	+0.096	3.3
BZX55C130	124	141	1.0	1000	5000	0.1	0.1	100	+0.096	3.0
BZX55C150	138	156	1.0	1200	5000	0.1	0.1	110	+0.096	2.6
BZX55C160	153	171	1.0	1500	5000	0.1	0.1	120	+0.096	2.5
BZX55C180	168	191	1.0	1800	5000	0.1	0.1	130	+0.096	2.2
BZX55C188	188	212	1.0	2000	5000	0.1	0.1	150	+0.096	2.0

RATINGS AND CHARACTERISTIC CURVES BZX55-SERIES

Breakdown characteristics



Admissible power dissipation versus ambient temperature
Valid provided that leads are kept at ambient temperature at a distance of 10mm from case

