

GBU8005 THRU GBU810




Glass Passivated Bridge Rectifiers

Reverse Voltage: 50 to 1000 Volts

Forward Current: 8.0 Ampere

RoHS Device

Halogen Free




Features

- Surge overload rating -200 amperes peak.
- Ideal for printed circuit board.

Mechanical Data

- Epoxy: UL 94V-0 rate flame retardant.
- Case: Molded plastic, GBU.
- Mounting position: Any.
- Weight: 3.91 grams (approx.).



Maximum ratings and electrical characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave ,60Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Parameter	Symbol	GBU 8005	GBU 801	GBU 802	GBU 804	GBU 806	GBU 808	GBU 810	Unit
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward (With heatsink Note2) Rectified Current @Tc=100°C (without heatsink)	I_{AV}	8.0 2.9							A
Peak Forward Surge Current, 8.3ms Single Half Sine-Wave Super Imposed On Rated Load (JEDEC Method)	I_{FSM}	200							A
Maximum Forward Voltage at 4.0A DC	V_F	1.0							V
Maximum DC Reverse Current @Tj=25°C At Rate DC Blocking Voltage @Tj=125°C	I_R	10.0 500							μA
I ² T Rating for Fusing(t<8.3ms)	I^2t	166							A ² s
Typical Junction Capacitance Per Element (Note 1)	C_J	60							pF
Typical Thermal Resistance	$R_{θJC}$	2.2							°C/W
Operating Temperature Range	T_J	-55 to +150							°C
Storage Temperature Range	T_{STG}	-55 to +150							°C

Notes:

1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
2. Device mounted on 75mm*75mm*1.6mm Cu plate heatsink.

Company reserves the right to improve product design , functions and reliability without notice.

Rev:1.0

Rating and Characteristics Curves

Fig.1 - Forward Current Derating Curve




Fig.2 - Maximum Non-Repetitive Surge Current




Fig.3 - Typical Junction Capacitance




Fig.4 - Typical Forward Characteristics






Fig.5 - Typical Reverse Characteristics



Marking Code

Part Number	Marking code
GBU8005	GBU8005
GBU801	GBU801
GBU802	GBU802
GBU804	GBU804
GBU806	GBU806
GBU808	GBU808
GBU810	GBU810



XXX / XXXX = Product type marking code
LEC = Longmacro Logo

Standard Packaging

Case Type	BULK PACK	
	BOX (pcs)	Carton (pcs)
GBU	250	3,000