


General Purpose Transistors PNP

RoHS Device

Halogen Free



Features



- Collector current: $I_C = -0.5A$
- High total power dissipation: $P_C = 300mW$
- Excellent HFE linearity.

Mechanical data

- Case: SOT-23, molded plastic.
- Mounting position: Any.

Circuit Diagram

1. Base
2. Emitter
3. Collector



Maximum Ratings (at $T_A = 25^\circ C$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Collector-base voltage	V_{CBO}	-40	V
Collector-emitter voltage	V_{CEO}	-25	V
Emitter-base voltage	V_{EBO}	-5	V
Collector current-continuous	I_C	-0.5	A
Collector power dissipation	P_C	0.3	W
Operation junction and storage temperature range	T_J, T_{STG}	-55 to +150	$^\circ C$

Electrical Characteristics (at $T_A=25^\circ\text{C}$ unless otherwise noted)



Parameter	Symbol	Conditions	Min	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C = -100\mu\text{A}$, $I_E = 0$	-40		V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C = -1\text{mA}$, $I_B = 0$	-25		V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E = -100\mu\text{A}$, $I_C = 0$	-5		V
Collector cut-off current	I_{CBO}	$V_{CB} = -40\text{V}$, $I_E = 0$		-0.1	μA
Collector cut-off current	I_{CEO}	$V_{CE} = -20\text{V}$, $I_B = 0$		-0.1	μA
Emitter cut-off current	I_{EBO}	$V_{EB} = -3\text{V}$, $I_C = 0$		-0.1	μA
DC current gain	$h_{FE(1)}$	$V_{CE} = -1\text{V}$, $I_C = -50\text{mA}$	120	400	
	$h_{FE(2)}$	$V_{CE} = -1\text{V}$, $I_C = -500\text{mA}$	50		
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = -500\text{mA}$, $I_B = -50\text{mA}$		-0.6	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C = -500\text{mA}$, $I_B = -50\text{mA}$		-1.2	V
Transition frequency	f_T	$V_{CE} = -6\text{V}$, $I_C = -20\text{mA}$, $f = 30\text{MHz}$	150		MHz

Classification of h_{FE} (1)

Rank	L	H	J
Range	120-200	200-350	300-400

Rating and Characteristic Curves

Fig.1 - Static Characteristic

Fig.2 - $h_{FE} — I_C$ 

Rating and Characteristic Curves

Fig.3 - $V_{BEsat} — I_c$




Fig.4 - $V_{CEsat} — I_c$




Fig.5 - $I_c — V_{BE}$




Fig.6 - $f_T — I_c$




Fig.7 - $C_{ob}/C_{ib} — V_{CB}/V_{EB}$





Fig.8 - $P_C — T_a$




Company reserves the right to improve product design, functions and reliability without notice.

Rev:1.0


Marking Code

Part Number	Marking Code
S8550	2TY



Suggested P.C.B. PAD Layout

SIZE	SOT-23	
	(mm)	(inch)
A	0.90	0.035
B	0.80	0.031
C	0.95	0.037
D	2.00	0.079
E	2.90	0.114




Note: 1. The pad layout is for reference purposes only.

Standard Packaging

Case Type	REEL PACK	
	REEL (pcs)	Reel Size (inch)
SOT-23	3,000	7

Reel Taping Specification



SOT-23	SYMBOL	A	B	C	d	D	D1	D2
	(mm)	3.15 ± 0.10	2.77 ± 0.10	1.22 ± 0.10	1.50 ± 0.10	178.00 ± 2.00	54.40 ± 1.00	13.00 ± 1.00
	(inch)	0.124 ± 0.004	0.109 ± 0.004	0.048 ± 0.004	0.059 ± 0.004	7.008 ± 0.079	2.142 ± 0.039	0.512 ± 0.039

SOT-23	SYMBOL	E	F	P	P0	P1	W	W1
	(mm)	1.75 ± 0.10	3.50 ± 0.10	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.10	8.00 ± 0.10	12.30 ± 1.00
	(inch)	0.069 ± 0.004	0.138 ± 0.004	0.157 ± 0.004	0.157 ± 0.004	0.079 ± 0.004	0.315 ± 0.004	0.484 ± 0.039