



MBS



FEATURES

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- Schottky technology
- Ideal for automated placement
- High surge current capability
- Built-in strain relief, ideal for automated placement
- High forward surge current capability
- High temperature soldering guaranteed: 260°C/10 seconds at terminals
- Green compound(halogen&Sb₂O₃ free)



Dimensions in inches and (millimeters)

MECHANICAL DATA

Case: Molded plastic body

Terminals: Plated leads solderable per MIL-STD-750, Method 2026

Polarity: Polarity symbols marked on case

Mounting Position: Any

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.


	SYMBOLS	SMB12S	SMB13S	SMB14S	SMB15S	SMB16S	SMB18S	SMB110S	SMB115S	SMB120S	UNITS	
Maximum repetitive peak reverse voltage	V _{RRM}	20	30	40	50	60	80	100	150	200	V	
Maximum RMS voltage	V _{RMS}	14	21	28	35	42	56	70	105	140	V	
Maximum DC blocking voltage	V _{DC}	20	30	40	50	60	80	100	150	200	V	
Maximum average forward rectified current at T _L (see fig.1)	I _{AV}	1.0									A	
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	I _{FSM}	30.0									A	
Maximum instantaneous forward voltage at 1.0A	V _F	0.55			0.70		0.85			0.95	V	
Maximum DC reverse current T _A =25°C at rated DC blocking voltage T _A =100°C	I _R	0.5							0.2		mA	
		10.0				5.0		2.0				
Typical junction capacitance (NOTE 1)	C _J	110			90							pF
Typical thermal resistance (NOTE 2)	R _{θJA}	85.0									°C/W	
Operating junction temperature range	T _J	-55 to +125					-55 to +150				°C	
Storage temperature range	T _{STG}	-55 to +150									°C	

Note:1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.

2. P.C.B. mounted with 0.2x0.2"(5.0x5.0mm) copper pad areas

RATINGS AND CHARACTERISTIC CURVES SMB12S THRU SMB120S

AVERAGE FORWARD RECTIFIED CURRENT,
AMPERES



PEAK FORWARD SURGE CURRENT,
AMPERES

