


DO-214AC



Dimensions in inches and (millimeters)

FEATURES

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- For surface mounted applications
- Metal silicon junction, majority carrier conduction
- Low power loss, high efficiency
- Built-in strain relief, ideal for automated placement
- High forward surge current capability
- High temperature soldering guaranteed: 260°C/10 seconds at terminals

MECHANICAL DATA

Case: JEDEC DO-214AC molded plastic body
Terminals: leads solderable per MIL-STD-750, Method 2026
Polarity: Color band denotes cathode end
Mounting Position: Any
Weight: 0.002 ounce, 0.07 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS


Ratings at 25°C ambient temperature unless otherwise specified.
 Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

	SYMBOLS	SS12L	SS13L	SS14L	SS15L	SS16L	SS18L	SS110L	UNITS	
Maximum repetitive peak reverse voltage	V _{RRM}	20	30	40	50	60	80	100	V	
Maximum RMS voltage	V _{RMS}	14	21	28	35	42	56	70	V	
Maximum DC blocking voltage	V _{DC}	20	30	40	50	60	80	100	V	
Maximum average forward rectified current at T _L (see fig.1)	I _(AV)	1.0							A	
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	I _{FSM}	30.0							A	
Maximum instantaneous forward voltage at 1.0A	V _F	0.45			0.5		0.7		V	
Maximum DC reverse current T _A =25°C at rated DC blocking voltage T _A =100°C	I _R	0.5					0.2		mA	
		10.0					5.0			
Typical junction capacitance (NOTE 1)	C _J	110			90					pF
Typical thermal resistance (NOTE 2)	R _{θJA}	75.0							°C/W	
Operating junction temperature range	T _J	-55 to +125					-55 to +150		°C	
Storage temperature range	T _{STG}	-55 to +150							°C	

Note: 1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.
 2. P.C.B. mounted with 0.2x0.2" (5.0x5.0mm) copper pad areas

RATINGS AND CHARACTERISTIC CURVES SS12L THRU SS110L

AVERAGE FORWARD RECTIFIED CURRENT,
AMPERES



PEAK FORWARD SURGE CURRENT,
AMPERES

